

QUOTE REQUEST



SOLAR LIGHTING SYSTEMS REQUEST

Customer: _____

Project: _____

Location: _____

Project Start Date: _____

Application:

Street / Roadway

Parking Lot

Walkway / Pathway

Sign / Billboard

Flag

Security

Bus Stop / Shelter

Other _____

Operation Schedule:

Dusk to Dawn

Dusk for ___ Hours

Split Time - Dusk for ___ Hours, Off, On ___ Hours Before Dawn

Dusk Activated for ___ at 100% then 50% until Dawn

Other: _____

Powder Coat (Optional Upgrade): _____

Pole Type:

Aluminum

Steel Galvanized

Concrete

Anchor Base

Direct Burial

Transformer Base

Notes / Requirements: _____

*Please provide as much details as possible such as dimensions, light level requirements, AutoCAD files, etc.

The next few pages goes over the standard fixtures in the SEPCO Solar Lighting Systems line. If another fixture is requested, please provide the part number in the notes section above.

QUOTE REQUEST

SOLAR LIGHTING SYSTEMS REQUEST



Overhead Fixtures

VPR - Viper

Viper Fixture is a shoebox / Cobrahead style fixture used for roadways, parking lots, area and perimeter lighting. The fixture is die cast aluminum, each LED has an individual optical lens for type II, III, IV, and V distributions, and comes in dark bronze, gray, and other colors, ranging from 15-70 Watts.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

ASL - Area Site Lighter

ASL Cutoff LED Fixture is a Cobrahead style fixture used for roadways, parking lots, area and perimeter lighting. The fixture is die cast aluminum, each LED has an individual optical lens and comes in dark bronze, black, silver and gray, ranging from 15-50 Watts. ASL2 ranges from 50-100 Watts.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

RAR - Ratio

Ratio Fixture is a shoebox style fixture used for roadways, parking lots, walkways, pathways, area and perimeter lighting. The fixture is die cast aluminum, each LED has an individual optical lens and comes in black, bronze, gray, silver, ranging from 15-100 Watts with multiple distribution patterns.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

DDL - Dusk to Dawn

Dusk to Dawn Security Fixture is a utility security style fixture used for roadways, parking lots areas and perimeters. The fixture is made from die-cast aluminum, uses a refractor lens for symmetrical or asymmetrical distribution and comes in gray and ranges from 10-20 Watts.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

QUOTE REQUEST

SOLAR LIGHTING SYSTEMS REQUEST



Decorative Fixtures

URB - Urban

Urban Fixture is a decorative style fixture used for roadways, parking lots, walkways, area and perimeters. The fixture uses cast aluminum housing, each LED has an individual optical lens for Type II, III, IV, and V distributions, and comes in black, bronze, green, gray and other colors, ranging from 15-55 Watts.

Wattage - _____ Distribution - _____ Color - _____ Finish - _____



LDN - London

London Fixture is a decorative acorn style fixture used for roadways, parking lots, walkways, area and perimeters. The fixture uses cast aluminum housing, each LED has an individual optical lens and comes in black, bronze, green, gray and white, ranging from 15-55 Watts.

Wattage - _____ Distribution - _____ Color - _____ Finish - _____



SLD - Slide

Slide Fixture is a decorative style fixture used for roadways, parking lots, walkways, area and perimeters. The fixture uses cast aluminum housing, each LED has an individual optical lens for type II, III, and V distributions, and comes in black, bronze, green, gray and other colors, ranging from 15-55 Watts.


Wattage - _____ Distribution - _____ Color - _____ Finish - _____



PWK - Pierwalk

Pierwalk Fixture is a decorative teardrop style fixture used for roadways, parking lots, walkways, area and perimeters. The fixture uses cast aluminum housing, each LED has an individual optical lens for type III and V distributions, and comes in black, bronze, green, gray and white, ranging from 15-55 Watts.

Wattage - _____ Distribution - _____ Color - _____ Finish - _____



QUOTE REQUEST

SOLAR LIGHTING SYSTEMS REQUEST



Flood Fixtures

AF - Alpha Flood

Alpha Flood Fixture is a flood style fixture used for perimeters, security, truck terminals, car lot, recreational sports, boat ramps and building floods. The fixture is die-cast aluminum with NEMA 2x2, 4x4, 5x5, 6x6, 6x4, and 4x6 optical assembly and comes in gray, bronze and other colors, ranging from 15-55 Watts.

Wattage - _____ Distribution - _____ Color - _____ Finish - _____



RFL - Medium Flood

RFL Ratio Flood Fixture is a flood style fixture used for signs and small area illumination. The fixture uses die-cast aluminum housing, high impact UV stabilized acrylic outer lens, with NEMA 2x2, 4x4, and 6x6 optical assembly, and comes in dark bronze, black, gray and other colors, ranging from 8-25 Watts, with larger options available for higher wattage needs.

Wattage - _____ Distribution - _____ Color - _____ Finish - _____



FLAB - Micro Flood

Micro Flood Fixture is a small flood style fixture used for flags, signs and landscapes. The fixture is die-cast aluminum, specular anodized aluminum reflectors and comes in bronze. The fixture is 3.4 Watts.

Wattage - 3.4 Distribution - Spot Color - 3k Finish - Bronze



QUOTE REQUEST

SOLAR LIGHTING SYSTEMS REQUEST



Wall / Ceiling Fixtures

LSQ - Lumasquare

LSQ Lumasquare Fixture is a ceiling mount fixture used for buildings, pavilions, stairwells, entryways, perimeters and corridors. The fixture is die cast aluminum, impact resistant acrylic diffuser for soft lumenance glow and comes in dark bronze and white, ranging from 10-30 Watts.



Wattage - _____ Finish - _____

LNC - Larado

Larado Fixture wall pack style fixture used for entryways and perimeters. The fixture is die cast aluminum, provides type III and IV distributions, and comes in dark bronze, gray, and other colors, ranging from 5-15 Watts.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

Landscape / Pathway Fixtures

BD - Bollard

BD Bollard fixture is used for walkways, courtyards and pathways. The fixture is extruded aluminum, provides symmetrical and asymmetrical optics for area lighting and comes in black, bronze and green, ranging from 3-31 Watts.



Wattage - _____ Distribution - _____ Color - _____ Finish - _____

ING - InGrade

InGrade Fixture is a small flood style fixture used for bus stops, bus shelters, walkways, pathways and lanscapes. The fixture is die-cast aluminum, specular anodized aluminum reflectors and comes in pewter. The fixture is 3.4 Watts.



Wattage - 3.4 Distribution - Spot Color - 3k Finish - Pewter